



The Print Works 35a Dane Road  
Coventry CV2 4JR  
United Kingdom.  
Tel +44(0)2475 090 133 Fax +44(0)2475 090 139  
sales@pretreatmentsolutions.com  
www.pretreatmentsolutions.com



## **TECHNICAL DATA SHEET PHOS-PREP® PP FINSOL**

### USE

Finsol is an evaporating Solvent designed to remove grease, smit and oily soils from metal parts, and finds application in Garages, General Metal Working and Fabrication Shops and any machinery or equipment where there are accumulations of grease.

### APPLICATION

Finsol is applied full strength at room temperature by non-atomising spray followed by a compressed air blow dry. It can also be applied by brushing on or wiping on followed by wiping off. May also be used by immersion as long as the holding tank has a lid.

### CONTROL

Finsol is used at full strength and no control is necessary.

### HANDLING

Operators should wear goggles, gloves and apron and use the Finsol in a well-ventilated area. Keep Finsol away from sources of heat, ignition and open flame. Avoid prolonged skin contact and store product away from direct sunlight.

### PRODUCT SAFETY DATA SHEET:

A safety data sheet is available

PHOS-PREP® PP Finsol is part of the PHOS-PREP® range of products for the treatment of iron, steel and aluminum at low temperatures.

Pre-Treatment Solutions Ltd continues to improve the quality and performance of its range of products and reserves the right to modify product formulations without prior notice.

**22/11/2017**